

BPOS-15 i3 7020U

Touch POS System

- Bezel-Free True Flat PCAP touch
- MSR / I-Button
- VFD customer display / 8" True-Flat LED monitor optional
- Mounted / Desktop type optional
- Slim stand
- Multiple interfaces
- Easy disassemble



Bezel-free True-Flat PCAP touch screen



With MSR, VFD customer display



With MSR, 8" True-Flat LED monitor



With MSR, 8" True-Flat LED monitor side view



With MSR, VFD customer display back view



Full set

Specification

CPU	Intel® Core™ Kaby Lake i3-7020U 2.3GHz 3MB cache 15W
Memory	8GB DDR3 1333MHz 1* SO-DIMM slot
HDD	MSATA 128GB SSD+slot SATA 2.5"
Size / Resolution	15" TFT-LED/ 1024×768
Touch Screen	True flat PCAP touch screen
Windows / Linux	Windows 10
Card Reader	MSR / I-button (Optional)
Customer Display	VFD (2*20 lines) (Optional)
2nd Display	8" true-flat LED monitor (800x600) (Optional)
Wireless Module	802.11a/b/g/n (Optional)
I/O Interface	4 USB 2.0, 2 USB 3.0, 1 COM, 1 Ethernet, 1 VGA, 1RJ11, 1 DC 12V out
Certificates	CE, FCC Class A, RoHS, CB
Working Temperature	0°C~40°C(32°F~104°F)
Carton Size(mm)	slim stand 425*185*420 (L*W*H)
G.W	6.5KGS